

# NX – IRONMAN™ WHEELS



- Compression molded to its maximum strength
- Machined slight crowned tread
- Durometer: Shore D 78-82
- Temperature range: -40°F to 250°F, enduring sharp temperature changes
- Black finish
- Excellent for power tow application

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	I.D. after Top Hat Spanner	Replace "" with desired bearing code.				
						Plain Bore	Roller Bearings	Tapered Bearings	Precision Bearing	Stainless Precision Bearing
2.5	1-3/4	1-15/16	1000	NX251B**		84	08, 9A			
4	2	2-3/16	2200	NX40JB4P	1/2	84	04, 09		6205	5S
5	2	2-3/16	2200	NX50JB4P	1/2			70	6205	5S
6	2	2-3/16	2200	NX60JB4P	1/2				6205	5S
			7200	NX60KB5P	3/4			6205		
	3	3-1/2*	7200	NX60LB5P	3/4				6205	
			7200	NX60LB7P	1			6207		
8	2	2-3/16	2200	NX80JB4P	1/2				6205	5S
			7200	NX80LB5P	3/4			6205		
	3	3-1/2*	7200	NX80LB7P	1				6207	
			8000	NX80NB8P	1-1/4			6208		
10	3	3-1/2*	7200	NX10LB5P	3/4				6205	
			7200	NX10LB7P	1					
	4	4-9/16*	8000	NX10NB8P	1-1/4				6208	
			7200	NX12LB5P	3/4			6205		
12	3	3-1/2*	7200	NX12LB7P	1				6207	
			8000	NX12NB8P	1-1/4			6208		

\* Hub Length after top head spanner

